Page: 1/15



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

1 Identification

- · Product identifier
- · Trade name: Natural Gas Condensate, Sweet
- · CAS Number:

68919-39-1

· Other means of identification:

Drips; Condensate; Field Condensate; Gas Well Condensate; High Pressure Inlet Liquids; Lease Condensate; Pipeline Liquids

- · Recommended use and restriction on use
- · Recommended use: Industrial uses.
- · Restrictions on use: No relevant information available.
- · Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Williams, Inc.
One Williams Center
Tulsa, OK 74172
USA
855-945-5762 (Toll-Free)
ehs@williams.com

· Emergency telephone number:

CHEMTREC

1-800-424-9300 (US/Canada)

+01 703-527-3887 (International)

2 Hazard(s) identification

Flam. Lig. 2 H225

· Classification of the substance or mixture

1 Idiiii Eiq. 2	11220	riiginy naminable liquid and vaper.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
Muta. 1A	H340	May cause genetic defects.
Carc. 1A	H350	May cause cancer.
Repr. 2	H361	Suspected of damaging fertility or the unborn child.
STOT SE 3	H336	May cause drowsiness or dizziness.
STOT RE 1	H372-H373	Causes damage to the hematopoietic system through prolonged or repeated exposure. May cause damage to the nervous system through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Highly flammable liquid and vapor.

Hazard pictograms:

(Cont'd. on page 2)

Page: 2/15



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

(Cont'd. of page 1)



GHS02 GHS07 GHS08

Signal word: DangerHazard statements:

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H372-H373 Causes damage to the hematopoietic system through prolonged or repeated exposure. May cause damage to the nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist/vapors/spray. P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P332+P313 If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

(Cont'd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

68919-39-1 Natural gas condensates

	1 Natural gas condensates	
· Compone		
142-82-5	Heptane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	10-30%
110-54-3	n-hexane Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336 Eye Irrit. 2B, H320	10-30%
109-66-0	pentane Flam. Liq. 2, H225 Asp. Tox. 1, H304 TSTOT SE 3, H336	10-30%
78-78-4	isopentane Flam. Liq. 1, H224 Asp. Tox. 1, H304 STOT SE 3, H336	5-20%
106-97-8	butane Flam. Gas 1, H220 Press. Gas, H280 Simple Asphyxiant	1-10%
75-28-5	isobutane Flam. Gas 1, H220 Press. Gas, H280 Simple Asphyxiant	0.1-5%
71-43-2	benzene Flam. Liq. 2, H225 Muta. 1B, H340; Carc. 1A, H350; STOT RE 1, H372; Asp. Tox. 1, H304 Skin Irrit. 2, H315; Eye Irrit. 2A, H319	0.4-2.1%
1330-20-7	xylenes Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335-H336 Eye Irrit. 2B, H320	0.1-1%
108-88-3	Toluene Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	0.1-1%

· Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

Page: 4/15



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

(Cont'd. of page 3)

4 First-aid measures

Description of first aid measures

· After inhalation:

Supply fresh air.

Provide oxygen treatment if affected person has difficulty breathing.

If experiencing respiratory symptoms: Call a poison center/doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· Most important symptoms and effects, both acute and delayed:

Breathing difficulty

Dizziness

Coughing

Causes skin and eye irritation.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Headache

Acne

Disorientation

· Danger:

Vapors may cause drowsiness and dizziness.

Condition may deteriorate with alcohol consumption.

May be fatal if swallowed and enters airways.

Causes damage to the hematopoietic system through prolonged or repeated exposure.

May cause damage to the nervous system through prolonged or repeated exposure.

Suspected of damaging fertility or the unborn child.

May cause cancer.

May cause genetic defects.

· Indication of any immediate medical attention and special treatment needed:

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Foam

Gaseous extinguishing agents

Carbon dioxide

Water fog / haze

Fire-extinguishing powder

(Cont'd. on page 5)





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

(Cont'd. of page 4)

· For safety reasons unsuitable extinguishing agents:

Water stream.

Water spray

· Special hazards arising from the substance or mixture

Highly flammable liquid and vapor.

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information: Eliminate all ignition sources if safe to do so.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Isolate area and prevent access.

Wear protective equipment. Keep unprotected persons away.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation.

Keep away from ignition sources.

Particular danger of slipping on leaked/spilled product.

· Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Prevent from spreading (e.g. by damming-in or oil barriers).

Report spills to authorities as required.

· Methods and material for containment and cleaning up

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Pick up mechanically.

Use spark-proof equipment.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling

· Precautions for safe handling:

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

· Information about protection against explosions and fires:

Highly flammable liquid and vapor.

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

(Cont'd. on page 6)

Page: 6/15



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

(Cont'd. of page 5)

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

- Further information about storage conditions: Keep containers tightly sealed.
- · Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

Components w	ith limit values that require monitoring at the workplace:	
142-82-5 Hepta	ne	
PEL (USA)	Long-term value: 2000 mg/m³, 500 ppm	
REL (USA)	Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800* mg/m³, 440* ppm *15-min	
TLV (USA)	Short-term value: 2050 mg/m³, 500 ppm Long-term value: 1640 mg/m³, 400 ppm	
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm	
EV (Canada)	Short-term value: 2045 mg/m³, 500 ppm Long-term value: 1635 mg/m³, 400 ppm	
LMPE (Mexico)	Short-term value: 500 ppm Long-term value: 400 ppm	
110-54-3 n-hex	ane	
PEL (USA)	Long-term value: 1800 mg/m³, 500 ppm	
REL (USA)	Long-term value: 180 mg/m³, 50 ppm	
TLV (USA)	Long-term value: 176 mg/m³, 50 ppm Skin; BEI	
EL (Canada)	Long-term value: 20 ppm Skin	
EV (Canada)	Long-term value: 176 mg/m³, 50 ppm	
LMPE (Mexico)	Long-term value: 50 ppm PIEL, IBE	
109-66-0 penta	ne	
PEL (USA)	Long-term value: 2950 mg/m³, 1000 ppm	
REL (USA)	Long-term value: 350 mg/m³, 120 ppm Ceiling limit value: 1800* mg/m³, 610* ppm *15-min	
TLV (USA)	Long-term value: 2950 mg/m³, 1000 ppm	
EL (Canada)	Long-term value: 1000 ppm	
EV (Canada)	Short-term value: 2,210 mg/m³, 750 ppm	

Page: 7/15



Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

		(Cont'd. of pa
	Long-term value: 1,770 mg/m³, 600 ppm	
,	Long-term value: 600 ppm	
78-78-4 isopen		
PEL (USA)	Long-term value: 2950 mg/m³, 1000 ppm	
TLV (USA)	Long-term value: 2950 mg/m³, 1000 ppm	
EL (Canada)	Long-term value: 1000 ppm	
EV (Canada)	Short-term value: 2,210 mg/m³, 750 ppm Long-term value: 1,770 mg/m³, 600 ppm	
LMPE (Mexico)	Long-term value: 600 ppm	
106-97-8 butan	e	
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm	
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm (EX)	
EL (Canada)	Short-term value: 1000 ppm EX	
EV (Canada)	Long-term value: 800 ppm revoked as of 01/01/18	
LMPE (Mexico)	Long-term value: 1000 ppm	
75-28-5 isobuta	ine	
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm (EX)	
EL (Canada)	Short-term value: 1000 ppm EX	
EV (Canada)	Long-term value: 800 ppm revoked as of 01/01/18	
LMPE (Mexico)	Long-term value: 1000 ppm	
1330-20-7 xyler	nes	
PEL (USA)	Long-term value: 435 mg/m³, 100 ppm	
REL (USA)	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV (USA)	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI	
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm	
EV (Canada)	Short-term value: 650 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
LMPE (Mexico)	Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE	
108-88-3 Tolue	ne	
PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
	10 mm pour por o m omit	(Cont'd. on pa

Page: 8/15



Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

DEI (110A)		(Cont'd. of page 7)	
REL (USA)	Short-term value: 560 mg/m³, 150 ppm		
	Long-term value: 375 mg/m³, 100 ppm		
TLV (USA)	Long-term value: 75 mg/m³, 20 ppm		
	BEI		
EL (Canada)	Long-term value: 20 ppm		
	R		
EV (Canada)	Long-term value: 20 ppm		
LMPE (Mexico)			
	A4, IBE		
71-43-2 benzen	ne		
PEL (USA)	Short-term value: 15* mg/m³, 5* ppm		
	Long-term value: 3* mg/m³, 1* ppm		
	*table Z-2 for exclusions in 29CFR1910.1028(d)		
REL (USA)	Short-term value: 1 ppm		
	Long-term value: 0.1 ppm		
	See Pocket Guide App. A		
TLV (USA)	Short-term value: 8 mg/m³, 2.5 ppm		
	Long-term value: 1.6 mg/m³, 0.5 ppm		
[Skin; BEI		
EL (Canada)	Short-term value: 2.5 ppm		
	Long-term value: 0.5 ppm Skin; ACGIH A1; IARC 1		
[] F\/ (Canada)			
EV (Canada)	Short-term value: 2.5 ppm Long-term value: 0.5 ppm		
	Skin		
LMPE (Mexico)			
LIVIF L (IVIEXICO)	Long-term value: 0.5 ppm		
	A1, PIEL, IBE		
· Ingredients with biological limit values:			
110-54-3 n-hexane BEI (USA) 0.4 mg/L			
	dium: urine		
1 1	e: end of shift at end of workweek		
	ameter: 2.5-Hexanedione without hydrolysis		
108-88-3 Tolue	ene		
BEI (USA) 0.02			
	dium: blood		
	e: prior to last shift of workweek		
Para	ameter: Toluene		
) mg/l		
	03 mg/L edium: urine		
	e: end of shift		
	ameter: Toluene		
	mg/g creatinine		
L Med	dium: urine		
		(Cont'd. on page 9)	

Page: 9/15



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

(Cont'd. of page 8)

Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

71-43-2 benzene

BEI (USA) 25 µg/g creatinine

Medium: urine

Time: end of shift Parameter

Parameter: S-Phenylmercapturic acid (background

500 µg/g creatinine Medium: urine Time: end of shift

Parameter: t,t-Muconic acid (background)

· Exposure controls

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately. Avoid contact with the eyes and skin.

- · Engineering controls: Provide adequate ventilation.
- · Breathing equipment:

Use suitable respiratory protective device when aerosol or mist is formed.



Self-contained respiratory protective device should be used in case of large spills or leaks.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Wear appropriate protective clothing.
- · Limitation and supervision of exposure into the environment

No relevant information available.

9 Physical and chemical properties

(Cont'd. on page 10)





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

	(Cont'd. of page 9)
· Information on basic physical and c	hemical properties
· Appearance:	
Form:	Liquid
Color: Odor:	Colorless to brownish-black Petroleum-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· рп-value. · Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	-29 to 427 °C (-20.2 °F)
· Flash point:	<10 °C (<50 °F)
Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
· Oxidizing properties:	Not determined.
· Vapor pressure at 37.8 °C (100 °F):	51-857 mmHg (1-16.5 psi)
 Density: Relative density: 	0.76 - 0.87
Vapor density:	Not determined.
Relative vapor density at 20 °C (68 °F)	
Evaporation rate:	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No relevant information available.

10 Stability and reactivity

- · Reactivity: No data available for self-reactivity.
- · Chemical stability: Stable under normal temperatures and pressures.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions

Highly flammable liquid and vapor.

(Cont'd. on page 11)



Page: 11/15

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

(Cont'd. of page 10)

Reacts with oxidizing agents.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Hazardous gases may be released if heated above the decomposition point.

· Conditions to avoid

Keep ignition sources away - Do not smoke.

Store away from oxidizing agents.

- · Incompatible materials No relevant information available.
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:		
71-43-2 benzene			
Oral	LD50	4,894 mg/kg (rat)	
Inhalative	LC50/4h	9,980 mg/l (mouse)	

- · Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Causes serious eye irritation.
- · Sensitization: Based on available data, the classification criteria are not met.
- \cdot IARC (International Agency for Research on Cancer):

71-43-2 benzene

1

· NTP (National Toxicology Program):

71-43-2 benzene

K

- · OSHA-Ca (Occupational Safety & Health Administration):
- 71-43-2 benzene

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- · Germ cell mutagenicity: May cause genetic defects.
- · Carcinogenicity: May cause cancer.
- · Reproductive toxicity: Suspected of damaging fertility or the unborn child.
- · STOT-single exposure: May cause drowsiness or dizziness.
- · STOT-repeated exposure:

Causes damage to the hematopoietic system through prolonged or repeated exposure. May cause damage to the nervous system through prolonged or repeated exposure.

· **Aspiration hazard:** May be fatal if swallowed and enters airways.

(Cont'd. on page 12)





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

(Cont'd. of page 11)

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes:

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- · Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number · DOT, ADR, IMDG, IATA	UN1268 or UN3295	
· UN proper shipping name		
· DOT, IATA	Petroleum distillates, n.o.s. or Petroleum products, n.o.s. or Hydrocarbons, liquids, n.o.s. PETROLEUM DISTILLATES, N.O.S.	
	or PETROLEUM PRODUCTS, N.O.S. or HYDROCARBONS, LIQUID, N.O.S.	
		(Cont'd. on page 13

Page: 13/15



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

(Cont'd. of page 12) · Transport hazard class(es) · DOT · Class 3 · Label 3 · ADR · Class 3 (F1) · Label · IMDG, IATA 3 · Class · Label 3 · Packing group · DOT, ADR, IMDG, IATA I (BP < 35 °C) or II (BP > 35 °C)· Environmental hazards Product contains environmentally hazardous substances: n-hexane · Marine pollutant: Yes · Special precautions for user Warning: Flammable liquids · Danger code (Kemler): · EMS Number: F-E,S-E · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA

(Cont'd. on page 14)





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

	(C	ont'd. of page 13		
	302 (extremely hazardous substances):			
Substanc	e is not listed.			
· Section 3	355 (extremely hazardous substances):			
Substanc	e is not listed.			
· Section 3	313 (Specific toxic chemical listings):			
Substanc	e is not listed.			
· TSCA (To	oxic Substances Control Act)			
Substanc	e is listed.			
· Propositi	on 65 (California)			
· Chemica	Is known to cause cancer:			
71-43-2 l	penzene			
Chemica	· Chemicals known to cause developmental toxicity for females:			
Substanc	e is not listed.			
· Chemica	Is known to cause developmental toxicity for males:			
	n-hexane			
71-43-2	benzene			
	Chemicals known to cause developmental toxicity:			
108-88-3				
71-43-2	benzene			
-	rironmental Protection Agency):			
108-88-3		II		
	n-hexane	II		
71-43-2	benzene	A, K/L		
	ernational Agency for Research on Cancer):			
71-43-2 l	penzene	1		
· Canadiar	Domestic Substances List (DSL) (Substances not listed.):			
Substanc	e is listed.			

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health Administration

Flam. Gas 1: Flammable gases - Category 1

Press. Gas: Gases under pressure - Compressed gas

(Cont'd. on page 15)

Page: 15/15



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 16, 2018 Revision: October 16, 2018

Trade name: Natural Gas Condensate, Sweet

(Cont'd. of page 14)

Flam. Liq. 1: Flammable liquids – Category 1 Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

Muta. 1A: Germ cell mutagenicity – Category 1A Muta. 1B: Germ cell mutagenicity – Category 1B Carc. 1A: Carcinogenicity – Category 1A Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by: ChemTel Inc.

Chemie inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com