

# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 08/16/2024

Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Wellhead Natural Gas

**Synonyms:** Wellhead Gas, Raw Gas, Methane, Residue Gas, Natural Gas Sweet, Marsh Gas, Fuel Gas, Petroleum Gas

#### 1.2. Intended Use of the Product

Industrial Uses

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

Williams Inc.

One Williams Center

Tulsa, OK 74172

855-945-5762

[www.williams.com](http://www.williams.com)

[ehs@williams.com](mailto:ehs@williams.com)

#### 1.4. Emergency Telephone Number

CHEMTREC:

1-800-424-9300 (US/Canada)

+01 703-527-3887 (International)

[Security.OperationsCenter@williams.com](mailto:Security.OperationsCenter@williams.com)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US/CA Classification

Flammable gases Category 1

H220

Gases under pressure Liquefied gas

H280

Simple Asphyxiant

#### 2.2. Label Elements

##### GHS-US/CA Labeling

**Hazard Pictograms (GHS-US/CA)** :



**Signal Word (GHS-US/CA)** :

Danger

**Hazard Statements (GHS-US/CA)** :

H220 - Extremely flammable gas.

H280 - Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

**Precautionary Statements (GHS-US/CA)** :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - In case of leakage, eliminate all ignition sources.

P403 - Store in a well-ventilated place.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

#### 2.3. Other Hazards

Contains a small amount of Hydrogen Sulfide, symptoms of overexposure are headaches, dizziness, nausea, coughing, respiratory irritation, eye irritation, skin irritation, pain in the nose, and loss of consciousness. Heating of the product may release higher amounts of Hydrogen Sulfide (H<sub>2</sub>S). Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Contact with gas escaping the container can cause frostbite.

#### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Methane	Marsh gas / Methyl hydride / Methane, compressed / Monomethylamine	(CAS-No.) 74-82-8	> 75	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Simple Asphy
Ethane	Ethyl hydride / ETHANE	(CAS-No.) 74-84-0	< 20	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Simple Asphy
Propane	Normal propane / PROPANE / n-Propane / R290	(CAS-No.) 74-98-6	< 10	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Carbon dioxide	CARBON DIOXIDE / Carbonic anhydride	(CAS-No.) 124-38-9	< 10	Press. Gas (Comp.), H280 Simple Asphy
n-Butane	Butane / BUTANE	(CAS-No.) 106-97-8	< 5	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Simple Asphy
Nitrogen	Nitrogen gas / Nitrogen, liquefied / NITROGEN / Nitrogen, compressed / nitrogen	(CAS-No.) 7727-37-9	< 5	Simple Asphy Press. Gas (Comp.), H280
Hydrogen sulfide	Hydrogen sulfide (H2S) / Hydrogen sulphide / Sulfur hydride / Dihydrogen sulphide / hydrogen sulfide / Hydrogen sulphide, hydrogen sulfide / Sulfane	(CAS-No.) 7783-06-4	< 0.0004	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Acute Tox. 2 (Inhalation:gas), H330 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT SE 1, H370 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of First-aid Measures

**General:** Rescuers must don respiratory protection before approaching exposed persons. Hydrogen sulfide has a characteristic rotten egg "sulfurous" odor with an odor threshold of less than 10 parts per billion. However, this odor should not be used as a warning property of toxic levels because H<sub>2</sub>S can overwhelm and deaden the sense of smell. Therefore, the smell of H<sub>2</sub>S should not be used as an indicator of a hazardous condition – a H<sub>2</sub>S meter or colorimetric indicating tubes are typically used to determine the concentration of H<sub>2</sub>S. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Give oxygen or artificial respiration if necessary. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 5 minutes. For brief contact with a small amount: Rewarm with body heat. Get immediate medical advice/attention. For extensive contact or a large amount: Immediately call a poison center/doctor and follow their advice. Specific treatment is urgent, incorrect first-aid practices will aggravate the injury. Protect affected area with a loose cover until proper medical treatment is received.

**Eye Contact:** Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

**Ingestion:** Ingestion is an unlikely route of exposure for a gas. Though risk of ingestion is extremely unlikely, in case of frostbite or freeze burns due to oral exposure seek immediate medical attention.

# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Contains a small amount of Hydrogen Sulfide, symptoms of overexposure are headaches, dizziness, nausea, coughing, respiratory irritation, eye irritation, skin irritation, pain in the nose, and loss of consciousness. Heating of the product may release higher amounts of Hydrogen Sulfide (H<sub>2</sub>S). May cause frostbite on contact with the liquid. Asphyxia by lack of oxygen: risk of death.

**Inhalation:** In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

**Skin Contact:** Contact with gas/liquid escaping the container can cause frostbite and freeze burns.

**Eye Contact:** Contact with gas/liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage.

**Ingestion:** Not considered a potential route of exposure, but contact with gas/liquid escaping the container can cause freeze burns and frostbite.

**Chronic Symptoms:** None expected under normal conditions of use.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Do not extinguish burning gas if flow cannot be shut off immediately. Extinguish secondary FIRES with appropriate materials.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Extremely flammable gas.

**Explosion Hazard:** Heating may cause an explosion. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapor-air mixture. Container may explode in heat of fire.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides, Nitrogen oxides. Hydrocarbons. Contains Sulfur, may release small amounts of hydrogen sulfide. Hydrogen sulfide is a highly flammable, explosive gas under certain conditions, is a toxic gas, and may be fatal. Gas can accumulate in the headspace of closed containers, use caution when opening sealed containers. Heating the product or containers can cause thermal decomposition of the product and release hydrogen sulfide.

**Other Information:** Use water spray to disperse vapors.

### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Ruptured cylinders may rocket. Do not allow product to spread into the environment. Eliminate every possible source of ignition. Do not get in eyes, on skin, or on clothing. Do not breathe gas.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Eliminate ignition sources. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Evacuate unnecessary personnel, isolate, and ventilate area. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Remove ignition sources. Stop leak, if possible without risk. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable. Ruptured cylinders may rocket. Do not pressurize, cut, or weld containers. Asphyxiating gas at high concentrations.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Do not breathe gas.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep in fireproof place. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling.

**Incompatible Materials:** Halogenated compounds. Strong acids, strong bases, strong oxidizers.

### 7.3. Specific End Use(s)

Industrial Uses

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Methane (74-82-8)		
USA ACGIH	ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
Nunavut	OEL STEL [ppm]	1250 ppm
Nunavut	OEL TWA [ppm]	1000 ppm
Northwest Territories	OEL STEL [ppm]	1250 ppm
Northwest Territories	OEL TWA [ppm]	1000 ppm
Saskatchewan	OEL STEL [ppm]	1250 ppm
Saskatchewan	OEL TWA [ppm]	1000 ppm
Ethane (74-84-0)		
USA ACGIH	ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
Alberta	OEL TWA [ppm]	1000 ppm
Nunavut	OEL STEL [ppm]	1250 ppm
Nunavut	OEL TWA [ppm]	1000 ppm
Northwest Territories	OEL STEL [ppm]	1250 ppm
Northwest Territories	OEL TWA [ppm]	1000 ppm
Saskatchewan	OEL STEL [ppm]	1250 ppm
Saskatchewan	OEL TWA [ppm]	1000 ppm
Propane (74-98-6)		
USA ACGIH	ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
USA OSHA	OSHA PEL (TWA) [1]	1800 mg/m <sup>3</sup>

# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>USA OSHA</b>	OSHA PEL (TWA) [2]	1000 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA)	1800 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL TWA [ppm]	1000 ppm
<b>USA IDLH</b>	IDLH [ppm]	2100 ppm (10% LEL)
<b>Alberta</b>	OEL TWA [ppm]	1000 ppm
<b>Nunavut</b>	OEL STEL [ppm]	1250 ppm
<b>Nunavut</b>	OEL TWA [ppm]	1000 ppm
<b>Northwest Territories</b>	OEL STEL [ppm]	1250 ppm
<b>Northwest Territories</b>	OEL TWA [ppm]	1000 ppm
<b>Québec</b>	VEMP (OEL TWA)	1800 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (OEL TWA) [ppm]	1000 ppm
<b>Saskatchewan</b>	OEL STEL [ppm]	1250 ppm
<b>Saskatchewan</b>	OEL TWA [ppm]	1000 ppm
<b>Carbon dioxide (124-38-9)</b>		
<b>USA ACGIH</b>	ACGIH OEL TWA [ppm]	5000 ppm
<b>USA ACGIH</b>	ACGIH OEL STEL [ppm]	30000 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) [1]	9000 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) [2]	5000 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA)	9000 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL TWA [ppm]	5000 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL)	54000 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL STEL [ppm]	30000 ppm
<b>USA IDLH</b>	IDLH [ppm]	40000 ppm
<b>Alberta</b>	OEL STEL	54000 mg/m <sup>3</sup>
<b>Alberta</b>	OEL STEL [ppm]	30000 ppm
<b>Alberta</b>	OEL TWA	9000 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA [ppm]	5000 ppm
<b>British Columbia</b>	OEL STEL [ppm]	15000 ppm
<b>British Columbia</b>	OEL TWA [ppm]	5000 ppm
<b>Manitoba</b>	OEL STEL [ppm]	30000 ppm
<b>Manitoba</b>	OEL TWA [ppm]	5000 ppm
<b>New Brunswick</b>	OEL STEL	54000 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL STEL [ppm]	30000 ppm
<b>New Brunswick</b>	OEL TWA	9000 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA [ppm]	5000 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL [ppm]	30000 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA [ppm]	5000 ppm
<b>Nova Scotia</b>	OEL STEL [ppm]	30000 ppm
<b>Nova Scotia</b>	OEL TWA [ppm]	5000 ppm
<b>Nunavut</b>	OEL STEL [ppm]	30000 ppm
<b>Nunavut</b>	OEL TWA [ppm]	5000 ppm
<b>Northwest Territories</b>	OEL STEL [ppm]	30000 ppm
<b>Northwest Territories</b>	OEL TWA [ppm]	5000 ppm
<b>Ontario</b>	OEL STEL [ppm]	30000 ppm
<b>Ontario</b>	OEL TWA [ppm]	5000 ppm
<b>Prince Edward Island</b>	OEL STEL [ppm]	30000 ppm
<b>Prince Edward Island</b>	OEL TWA [ppm]	5000 ppm
<b>Québec</b>	VECD (OEL STEL)	54000 mg/m <sup>3</sup>
<b>Québec</b>	VECD (OEL STEL) [ppm]	30000 ppm
<b>Québec</b>	VEMP (OEL TWA)	9000 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (OEL TWA) [ppm]	5000 ppm

# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Saskatchewan	OEL STEL [ppm]	30000 ppm
Saskatchewan	OEL TWA [ppm]	5000 ppm
Yukon	OEL STEL	27000 mg/m <sup>3</sup>
Yukon	OEL STEL [ppm]	15000 ppm
Yukon	OEL TWA	9000 mg/m <sup>3</sup>
Yukon	OEL TWA [ppm]	5000 ppm
<b>n-Butane (106-97-8)</b>		
USA ACGIH	ACGIH OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
USA NIOSH	NIOSH REL (TWA)	1900 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL TWA [ppm]	800 ppm
USA IDLH	IDLH [ppm]	1600 ppm (>10% LEL)
Alberta	OEL TWA [ppm]	1000 ppm
British Columbia	OEL STEL [ppm]	1000 ppm (Butane, all isomers)
Manitoba	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
New Brunswick	OEL TWA	1900 mg/m <sup>3</sup>
New Brunswick	OEL TWA [ppm]	800 ppm
Newfoundland & Labrador	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
Nova Scotia	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
Nunavut	OEL STEL [ppm]	1250 ppm (Butane, all isomers)
Nunavut	OEL TWA [ppm]	1000 ppm (Butane, all isomers)
Northwest Territories	OEL STEL [ppm]	1250 ppm (Butane, all isomers)
Northwest Territories	OEL TWA [ppm]	1000 ppm (Butane, all isomers)
Ontario	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, all isomers))
Prince Edward Island	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
Québec	VEMP (OEL TWA)	1900 mg/m <sup>3</sup>
Québec	VEMP (OEL TWA) [ppm]	800 ppm
Saskatchewan	OEL STEL [ppm]	1250 ppm (Butane, all isomers)
Saskatchewan	OEL TWA [ppm]	1000 ppm (Butane, all isomers)
Yukon	OEL STEL	1600 mg/m <sup>3</sup>
Yukon	OEL STEL [ppm]	750 ppm
Yukon	OEL TWA	1400 mg/m <sup>3</sup>
Yukon	OEL TWA [ppm]	600 ppm
<b>Nitrogen (7727-37-9)</b>		
USA ACGIH	ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
<b>Hydrogen sulfide (7783-06-4)</b>		
USA ACGIH	ACGIH OEL TWA [ppm]	1 ppm
USA ACGIH	ACGIH OEL STEL [ppm]	5 ppm
USA OSHA	OSHA PEL C [ppm]	20 ppm
USA OSHA	Acceptable Maximum Peak Above The Acceptable Ceiling Concentration For An 8-Hr Shift	50 ppm Peak (10 minutes once, only if no other measurable exposure occurs)
USA NIOSH	NIOSH REL (Ceiling)	15 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL C [ppm]	10 ppm
USA IDLH	IDLH [ppm]	100 ppm
Alberta	OEL C	21 mg/m <sup>3</sup>
Alberta	OEL Ceiling [ppm]	15 ppm
Alberta	OEL TWA	14 mg/m <sup>3</sup>
Alberta	OEL TWA [ppm]	10 ppm
British Columbia	OEL Ceiling [ppm]	10 ppm
Manitoba	OEL STEL [ppm]	5 ppm

# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Manitoba	OEL TWA [ppm]	1 ppm
New Brunswick	OEL STEL	21 mg/m <sup>3</sup>
New Brunswick	OEL STEL [ppm]	15 ppm
New Brunswick	OEL TWA	14 mg/m <sup>3</sup>
New Brunswick	OEL TWA [ppm]	10 ppm
Newfoundland & Labrador	OEL STEL [ppm]	5 ppm
Newfoundland & Labrador	OEL TWA [ppm]	1 ppm
Nova Scotia	OEL STEL [ppm]	5 ppm
Nova Scotia	OEL TWA [ppm]	1 ppm
Nunavut	OEL STEL [ppm]	15 ppm
Nunavut	OEL TWA [ppm]	10 ppm
Northwest Territories	OEL STEL [ppm]	15 ppm
Northwest Territories	OEL TWA [ppm]	10 ppm
Ontario	OEL STEL [ppm]	15 ppm
Ontario	OEL TWA [ppm]	10 ppm
Prince Edward Island	OEL STEL [ppm]	5 ppm
Prince Edward Island	OEL TWA [ppm]	1 ppm
Québec	VECD (OEL STEL)	21 mg/m <sup>3</sup>
Québec	VECD (OEL STEL) [ppm]	15 ppm
Québec	VEMP (OEL TWA)	14 mg/m <sup>3</sup>
Québec	VEMP (OEL TWA) [ppm]	10 ppm
Saskatchewan	OEL STEL [ppm]	15 ppm
Saskatchewan	OEL TWA [ppm]	10 ppm
Yukon	OEL STEL	27 mg/m <sup>3</sup>
Yukon	OEL STEL [ppm]	15 ppm
Yukon	OEL TWA	15 mg/m <sup>3</sup>
Yukon	OEL TWA [ppm]	10 ppm
<b>Aliphatic hydrocarbon gases: Alkanes (C1-4) (Not Applicable)</b>		
Nunavut	OEL STEL [ppm]	1250 ppm
Nunavut	OEL TWA [ppm]	1000 ppm
Northwest Territories	OEL STEL [ppm]	1250 ppm
Northwest Territories	OEL TWA [ppm]	1000 ppm
Saskatchewan	OEL STEL [ppm]	1250 ppm
Saskatchewan	OEL TWA [ppm]	1000 ppm
<b>Aliphatic hydrocarbon gases, alkane (C2-4) (Not Applicable)</b>		
Alberta	OEL TWA [ppm]	1000 ppm

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Gas detectors should be used when flammable gases or vapors may be released. Oxygen detectors should be used when asphyxiating gases may be released.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Respiratory protection of the dependent type.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

**Hand Protection:** Wear protective gloves. If material is cold, wear thermally resistant protective gloves.

**Eye and Face Protection:** Faceshield as determined by task. Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Respiratory Protection:** Use a NIOSH-approved self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

**Thermal Hazard Protection:** Wear thermally resistant protective clothing.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Gas
Appearance	: Colorless
Odor	: Gasoline-like or natural gas odor, may contain hydrogen sulfide which has a rotten egg odor
Odor Threshold	: < 1 ppm
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: -157 °C (-250.6 °F)
Flash Point	: -187 °C (-304.6 °F)
Auto-ignition Temperature	: > 288 °C (550.4 °F)
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Extremely flammable gas
Lower Flammable Limit	: 3 %
Upper Flammable Limit	: 17 %
Vapor Pressure	: 40 mm Hg (0.8 psi)
Relative Vapor Density at 20°C	: No data available
Relative Density	: > 1 (air =1)
Specific Gravity	: No data available
Solubility	: Water: Not miscible or difficult to mix
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available
Explosive Properties	: Contains gas under pressure; may explode if heated

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity:

Hazardous reactions will not occur under normal conditions.

### 10.2. Chemical Stability:

Contains gas under pressure; may explode if heated.

### 10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

### 10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, open flames, sources of ignition and incompatible materials.

### 10.5. Incompatible Materials:

Halogenated compounds. Strong acids, strong bases, strong oxidizers.

### 10.6. Hazardous Decomposition Products:

Thermal decomposition may produce: Carbon oxides, Nitrogen oxides. Hydrocarbons. Contains Sulfur, may release small amounts of hydrogen sulfide. Hydrogen sulfide is a highly flammable, explosive gas under certain conditions, is a toxic gas, and may be fatal. Gas can accumulate in the headspace of closed containers, use caution when opening sealed containers. Heating the product or containers can cause thermal decomposition of the product and release hydrogen sulfide.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

### LD50 and LC50 Data:

No additional information available



# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Skin Corrosion/Irritation:** Not classified  
**Eye Damage/Irritation:** Not classified  
**Respiratory or Skin Sensitization:** Not classified  
**Germ Cell Mutagenicity:** Not classified  
**Carcinogenicity:** Not classified  
**Specific Target Organ Toxicity (Repeated Exposure):** Not classified  
**Reproductive Toxicity:** Not classified  
**Specific Target Organ Toxicity (Single Exposure):** Not classified  
**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

**Symptoms/Injuries After Skin Contact:** Contact with gas/liquid escaping the container can cause frostbite and freeze burns.

**Symptoms/Injuries After Eye Contact:** Contact with gas/liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage.

**Symptoms/Injuries After Ingestion:** Not considered a potential route of exposure, but contact with gas/liquid escaping the container can cause freeze burns and frostbite.

**Chronic Symptoms:** None expected under normal conditions of use.

### 11.2. Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

<b>Methane (74-82-8)</b>	
LD50 Dermal Rat	> 2000 mg/kg
LC50 Inhalation Rat	539600 ppm (Exposure time: 2 h)
<b>Ethane (74-84-0)</b>	
LC50 Inhalation Rat	> 800000 ppm/4h
<b>Propane (74-98-6)</b>	
LC50 Inhalation Rat	> 800000 ppm (Exposure time: 15 min)
<b>n-Butane (106-97-8)</b>	
LC50 Inhalation Rat	30957 mg/m <sup>3</sup> (Exposure time: 4 h)
LC50 Inhalation Rat	276798.8 ppm
<b>Hydrogen sulfide (7783-06-4)</b>	
LC50 Inhalation Rat	444 ppm/4h

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General:** Not classified.

<b>Hydrogen sulfide (7783-06-4)</b>	
LC50 Fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC50 Fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

### 12.2. Persistence and Degradability

<b>Wellhead Natural Gas</b>	
Persistence and Degradability	Not established.

### 12.3. Bioaccumulative Potential

<b>Wellhead Natural Gas</b>	
Bioaccumulative Potential	Not established.
<b>Methane (74-82-8)</b>	
Partition coefficient n-octanol/water (Log Pow)	1.09
<b>Ethane (74-84-0)</b>	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 at 20 °C / 68 °F (at pH 7)
<b>Propane (74-98-6)</b>	

# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Partition coefficient n-octanol/water (Log Pow)	1.09 at 20 °C / 68 °F (at pH 7)
<b>Carbon dioxide (124-38-9)</b>	
BCF Fish 1	(no bioaccumulation)
Partition coefficient n-octanol/water (Log Pow)	0.83
<b>n-Butane (106-97-8)</b>	
Partition coefficient n-octanol/water (Log Pow)	2.31 at 20 °C / 68 °F (at pH 7)
<b>Hydrogen sulfide (7783-06-4)</b>	
BCF Fish 1	(no bioaccumulation expected)
Partition coefficient n-octanol/water (Log Pow)	0.45 (at 25 °C / 77 °F)

### 12.4. Mobility in Soil

No additional information available

### 12.5. Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Sewage Disposal Recommendations:** Do not dispose of waste into sewer. Do not empty into drains.

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable. Empty gas cylinders should be returned to the vendor for recycling or refilling. Do not puncture or incinerate container.

**Ecology - Waste Materials:** Avoid release to the environment.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

**Proper Shipping Name** : NATURAL GAS, COMPRESSED (with high methane content)  
**Hazard Class** : 2.1  
**Identification Number** : UN1971  
**Label Codes** : 2.1  
**ERG Number** : 115



### 14.2. In Accordance with IMDG

**Proper Shipping Name** : NATURAL GAS, COMPRESSED (with high methane content)  
**Hazard Class** : 2.1  
**Identification Number** : UN1971  
**Label Codes** : 2.1  
**EmS-No. (Fire)** : F-D  
**EmS-No. (Spillage)** : S-U



### 14.3. In Accordance with IATA

**Proper Shipping Name** : NATURAL GAS, COMPRESSED (with high methane content)  
**Hazard Class** : 2.1  
**Identification Number** : UN1971  
**Label Codes** : 2.1  
**ERG Code (IATA)** : 10L



# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 14.4. In Accordance with TDG

**Proper Shipping Name** : NATURAL GAS, COMPRESSED (with high methane content)  
**Hazard Class** : 2.1  
**Identification Number** : UN1971  
**Label Codes** : 2.1



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

<b>Wellhead Natural Gas</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Physical hazard - Gas under pressure Health hazard - Simple asphyxiant
<b>Methane (74-82-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
<b>Ethane (74-84-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
<b>Propane (74-98-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
<b>Carbon dioxide (124-38-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
<b>n-Butane (106-97-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
<b>Nitrogen (7727-37-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
<b>Hydrogen sulfide (7783-06-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on the United States SARA Section 302 Subject to reporting requirements of United States SARA Section 313	
<b>CERCLA RQ</b>	100 lb
<b>SARA Section 302 Threshold Planning Quantity (TPQ)</b>	500 lb
<b>SARA Section 313 - Emission Reporting</b>	1 %

### 15.2. US State Regulations

<b>Methane (74-82-8)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
<b>Ethane (74-84-0)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
<b>Propane (74-98-6)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
<b>Carbon dioxide (124-38-9)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
<b>n-Butane (106-97-8)</b>

# Wellhead Natural Gas

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Massachusetts - Right To Know List

### **Nitrogen (7727-37-9)**

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Massachusetts - Right To Know List

### **Hydrogen sulfide (7783-06-4)**

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Massachusetts - Right To Know List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

## 15.3. Canadian Regulations

### **Methane (74-82-8)**

Listed on the Canadian DSL (Domestic Substances List)

### **Ethane (74-84-0)**

Listed on the Canadian DSL (Domestic Substances List)

### **Propane (74-98-6)**

Listed on the Canadian DSL (Domestic Substances List)

### **Carbon dioxide (124-38-9)**

Listed on the Canadian DSL (Domestic Substances List)

### **n-Butane (106-97-8)**

Listed on the Canadian DSL (Domestic Substances List)

### **Nitrogen (7727-37-9)**

Listed on the Canadian DSL (Domestic Substances List)

### **Hydrogen sulfide (7783-06-4)**

Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 06/28/2023

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

### GHS Full Text Phrases:

H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H319	Causes serious eye irritation
H330	Fatal if inhaled
H335	May cause respiratory irritation
H370	Causes damage to organs
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*